

57-DVRS50N



*Excellence*  
Direct Vent Gas Fireplace



**Excellence, Ambience and Style**

Specifically designed to fit in tight spaces where other units can't, Brigantia's all new 57-DVRS50N direct vent gas fireplace adds a touch of style and warmth to any room.

57-DVRS50N

# Excellence

## Direct Vent Gas Fireplace



### SPECIFICATIONS

Input Rating	
Natural Gas	21,000 - 50,000 BTU/HR / 6.1 - 14.7 KW
Propane	19,000 - 50,000 BTU/HR / 5.6 - 14.7 KW

Efficiencies	
Maximum Efficiency	84%
P4	70%

Standard Features	
Remote Control	Adjustable flame, smart thermostat
Interior Lining	Black steel
Ceramic Glass Door	Included
Viewing Area	54" W x 16" H
Vent Size	5" x 8" rigid or flex
Burner Type	Wall to Wall Steel Pan
Firebox and Host Shell Construction	Welded/rivet and gasket, silicone free Host shell has removable firebox which allows the shell to be installed without the firebox
Warranty	Limited lifetime

Options	
Interior Lining	Reflective Glass Panel
Propane Conversion Kit	Optional
Door	Black or Brushed Nickel
Surround	Black or Brushed Nickel

Clearance to Combustibles	
Framing Dimensions	66-1/2" (1689mm) W x 42" (1067mm) H x 6" (152mm) D
Room Clearances Measured to Outer Shell	Sidewall 18" (457mm) Floor 5" (127mm) Ceiling 36" (914mm) Mantel = 9" (229mm) (Based on 8" (203mm) deep mantel)

Host Shell clearance to combustibles 0" to standoffs. See owner's manual for framing instructions and clearance to combustible guides.

All information on this literature is subject to change at the discretion of the manufacturer.

### FRONT PANELS



Brushed Nickel Door with Brushed Nickel Surround



Black Door with Black Surround



Brushed Nickel Door with Black Surround



Black Door with Brushed Nickel Surround

